

IPR-80961RB

Terminal Printer

Reliable. Fast. Efficient.
Built for Your Business.

High-speed terminal printer with robust design and multiple interfaces, ideal for a wide range of applications and industries.



High Speed Printing
Up to 300 mm/s

Durable & Reliable
Solid metal hinges
MCBF 6 Million lines
Auto cutter 1 Million cuts

High Resolution
203 dpi (8 dots/mm)
72 mm or 64 mm effective width

Connectivity Options
USB / Serial / Parallel / Ethernet

USB Serial (RS232) Parallel Ethernet (LAN)

Easy Integration
ESC/POS, OPOS driver support
Wall-hangings included

Premium Craftsmanship
Senior mould made by Germany
imported material, excellent detail processing

KEY SPECIFICATIONS

Printing Method	Direct Thermal
Printing Speed	300 mm/s
Resolution	203 dpi (8 dots/mm)
Effective Printing Width	72 mm or 64 mm
Printing Density	504 dots/line or 576 dots/line
Paper Width	79.5 ± 0.5 mm
Paper Roll Diameter	Max. 80.0 mm
Interfaces	USB, Serial, Parallel, Ethernet
Auto Cutter Life	1 Million cuts
Thermal Head Life	100 Million impulses (100km)
Power Supply	DC 24V, 2.5A
Dimensions (WxDxH)	195 x 145 x 148 mm

IDEAL FOR MULTIPLE INDUSTRIES & APPL.



FOOD & BEVERAGE

- Order receipts
- Kitchen orders (KDS)
- Queue management tickets



RETAIL & WHOLESALE

- POS receipts
- Price labels
- Returns & exchange slips



SERVICE & HOSPITALITY

- Admission tickets
- Queue management tickets
- Service receipts



LOGISTICS & WAREHOUSE

- Shipping labels
- Picking list
- Inventory & stock tracking

OTHER SPECIAL APPLICATIONS

BANKS & GOVERNMENT
Queue management
number ticket system

HOSPITALS & CLINICS
Registration receipts,
billing slips or
medication number tickets



PRINT SPECIFICATIONS

Print	Character Set	GB18030 (Simplified Chinese)
	Print Font	ASCII Font A : 12x24
	Character Per Line	Font A-42 lines or 48 lines Font B-56 lines or 64 lines Chinese-21 lines or 24 lines
Paper Spec	Paper Width	79.5 ± 0.5 mm
	Paper Roll Diameter	Max. 80.0 mm
	Paper Loading	Easy paper loading
Barcodes	Barcode Type	UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128

RELIABILITY & ENVIRONMENT

Reliability	MCBF	6 million lines	Driver	WIN98 / WIN2000 / WINNT / WINXP / OPOS / WIN7 / WIN8	
	Thermal Printing Head	100 million impulses (100km)		Cash Drawer Control	DC 24V, 1A
	Auto Cutter	1 million cuts		Certificate	FCC, CE, 3C
Environmental	Temperature	Working: 0~45°C Storage: -10~50°C	Dimension (LxWxH)	195 x 145 x 148 mm	
	Humidity	Working: 10~80% Storage: 10~90% (paper excluded)			

SYSTEM & CERTIFICATION

Power Supply	DC 24V, 2.5A
Interface	USB, Serial, Parallel, Ethernet
Paper Out Detection Function	Optional
Emulation	ESC / POS / OPOS



INTERESTED?

Let's discuss how the IPR-80961RB can improve your business efficiency.

CONTACT US TODAY!



TEL: +886-277087199



Email: sales@ipotech.com.tw



Website: <https://www.ipotech.com.tw/>



Scan to Visit Website